



**ProX Butterfly Weave C68DB Ultra Light Full Carbon Spoke Disc Road Wheels**

Model	C68DB-BRD28-33C-CS1	C68DB-BRD28-38C-CS1	C68DB-BRD28-45C-CS1	C68DB-BRD28-50C-CS1	C68DB-BRD28-55C-CS1
Rim Drawing					
Rim Depth	33mm	38mm	45mm	50mm	55mm
Rim Width	28mm Outer (21mm Inner)	28mm Outer (21mm Inner)	28mm Outer (21mm Inner)	28mm Outer (21mm Inner)	28mm Outer (21mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX C68DB	ProX C68DB	ProX C68DB	ProX C68DB	ProX C68DB
Front Size	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle
Rear Size	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle
Spoke	ProX CS1	ProX CS1	ProX CS1	ProX CS1	ProX CS1
Tire Size (Recommended)	700*28C-45C	700*28C-45C	700*28C-45C	700*28C-45C	700*28C-45C
Weight (+/-3%)	1186g	1216g	1256g	1296g	1306g



28mm Outer width

Undulating rim depth optional:  
30-35mm  
45-50mm  
60-65mm

Finish optional:  
Non-paint  
Pearl white

Full carbon spoke width:  
3.1mm  
5.5mm

ProX C67DB Disc Hubs-Ceramic Bearings  
Shimano 11/12s or SRAM 12s XDR




36T Ratchet Freehub System

Precise Hand-built

Front 21/Rear 21 Spokes (2:1 ratio)



## ProX Super Light C67DB Ratchet System Full Carbon Spoke Road Wheels (Undulating Rims)


Model	C67DB-NRD28-305-CS1 C67DB-NRD28-305-White-CS1	C67DB-NRD28-450-CS1 C67DB-NRD28-450-White-CS1	C67DB-NRD28-605-CS1 C67DB-NRD28-605-White-CS1
Rim Drawing			
Rim Depth	30-35mm	45-50mm	60-65mm
Rim Width	28mm Outer (21mm Inner)	28mm Outer (21mm Inner)	28mm Outer (21mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX C67DB	ProX C67DB	ProX C67DB
Front Size	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle
Rear Size	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle
Spoke	ProX CS1	ProX CS1	ProX CS1
Tire Size (Recommended)	700*28C-45C	700*28C-45C	700*28C-45C
Weight (+/-3%)	1175g/1265g	1295g/1385g	1420g/1520g

**23mm Inner Width**

**Sapim CX-Ray Spokes  
Super Aero & Light**

**Front 24/Rear 24 Spokes**

**Tubeless Ready**



**DT Swiss Hubs Optional**

**ProX C53DB Hubs Ceramic Bearings  
54T Ratchet Freehub System**

**Freehub Body Options:  
Shimano HG 11/12s  
SRAM XDR  
Shimano Micro Spline Road (MSR)  
Campagnolo N3W**

**Compatible For 700\*30C-50C Tire**

**ProX Light Weight C53DB Carbon Road Wheels High Performance Ratchet Freehub Road Wheels**

Model	C53DB-PRD923-38C-Ray	C53DB-PRD923-45C-Ray	C53DB-PRD923-50C-Ray	C53DB-PRD923-55C-Ray	C53DB-PRD923-60C-Ray
Rim Drawing					
Rim Depth	38mm	45mm	50mm	55mm	60mm
Rim Width	28.5mm Outer (23mm Inner)	28.5mm Outer (23mm Inner)	28.5mm Outer (23mm Inner)	28.5mm Outer (23mm Inner)	28.5mm Outer (23mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX C53DB	ProX C53DB	ProX C53DB	ProX C53DB	ProX C53DB
Front Size	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle
Rear Size	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle
Spoke	Sapim CX-Ray	Sapim CX-Ray	Sapim CX-Ray	Sapim CX-Ray	Sapim CX-Ray
Tire Size (Recommended)	700*30C-50C	700*30C-50C	700*30C-50C	700*30C-50C	700*30C-50C
Weight (+/-3%)	1302g	1322g	1382g	1442g	1482g



Undulating Rim Depth

With Decal and Without Decal Optional

Pillar 1423 spokes, Aero & strong

Front 24/Rear 24 Spokes

DT Swiss Hubs Optional



ProX C52DB Disc Hubs-Ceramic Bearings

36T Ratchet Freehub System  
Shimano HG 11/12s, Micro Spline,  
SRAM XDR 12s, Campagnolo N3W

28mm Width Carbon Rims



### ProX Mid-range C52DB Ratchet System Hub Carbon Road Wheels (Undulating Rims)

<b>Model</b>	<b>C52DB-URD28-450-1423</b> <b>C52DB-NRD28-450-1423</b>	<b>C52DB-URD26-450-1423</b> <b>C52DB-NRD26-450-1423</b>
<b>Rim Drawing</b>		
<b>Rim Depth</b>	45-50mm	45-50mm
<b>Rim Width</b>	28mm Outer (21mm Inner)	25.5mm Outer (19mm Inner)
<b>Tire Type</b>	Tubeless or Clincher	Tubeless or Clincher
<b>Hub</b>	ProX C52DB	ProX C52DB
<b>Front Size</b>	12*100mm Thru-Axle	12*100mm Thru-Axle
<b>Rear Size</b>	12*142mm Thru-Axle	12*142mm Thru-Axle
<b>Spoke</b>	Pillar 1423	Pillar 1423
<b>Tire Size (Recommended)</b>	700*28C-45C	700*25C-40C
<b>Weight (+/-3%)</b>	1600g/1500g	1580g/1480g

**25mm Width Carbon Rims**

**Pillar 1423 Spokes, Aero&Strong**

**Front 24/Rear 24 Spokes**

**ProX 98DB Economical Disc Brake Hubs**

**6-Pawl Freehub System  
Shimano 11/12s or SRAM 12s XDR Optional**

**Compatible for 700\*25C-45C tire (tubeless ready)**



**ProX Affordable 98DB Carbon Road Wheels (25mm Width)**

Model	98DB-PRD25-38C-1423	98DB-PRD25-45C-1423	98DB-PRD25-50C-1423	98DB-PRD25-60C-1423	98DB-PRD25-80C-1423
Rim Drawing					
Rim Depth	38mm	45mm	50mm	60mm	80mm
Rim Width	25mm Outer (18mm Inner)	25mm Outer (18mm Inner)	25mm Outer (18mm Inner)	25mm Outer (18mm Inner)	25mm Outer (18mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX 98DB	ProX 98DB	ProX 98DB	ProX 98DB	ProX 98DB
Front Size	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle
Rear Size	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle
Spoke	Pillar 1423	Pillar 1423	Pillar 1423	Pillar 1423	Pillar 1423
Tire Size (Recommended)	700*25C-45C	700*25C-45C	700*25C-45C	700*25C-45C	700*25C-45C
Weight (+/-3%)	1467g	1527g	1587g	1727g	2007g

**DT Swiss Hubs Optional**  
**G71DB Disc Brake Hubs- Steel Bearings**  
**Shimano 11/12s, MSR or SRAM XDR Optional**

Compatible For 700\*35C-50C Tire

Bladed Carbon Spokes (ProX CS1)  
 Only 2.9g/pc!

Precise Wheels Handbuilt

36T Ratchet Freehub System

26mm Inner Width/31.5mm Outer Width

Front 24/Rear 24 Spokes



**ProX Super Light G71DB Gravel Wheels Full Carbon Spoke Gravel Bike Wheels**

Model	<b>G71DB-PXG26-40C-CS1</b>	<b>G71DB-PXG26-45C-CS1</b>	<b>G71DB-PXG26-50C-CS1</b>
Rim Drawing			
Rim Depth	40mm	45mm	50mm
Rim Width	31.5mm Outer (26mm Inner)	31.5mm Outer (26mm Inner)	31.5mm Outer (26mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX G71DB	ProX G71DB	ProX G71DB
Front Size	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle
Rear Size	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle
Spoke	ProX CS1	ProX CS1	ProX CS1
Tire Size (Recommended)	700*35C-50C	700*35C-50C	700*35C-50C
Weight (+/-3%)	1292g	1332g	1372g

**DT Swiss Hubs Optional**

**ProX C52DB Disc Hubs-Ceramic Bearings**

**36T Ratchet Freehub System  
Shimano HG 11/12s, Micro Spline,  
SRAM XDR 12s, Campagnolo N3W**

**Compatible for 700\*35C-50C tire  
(tubeless ready)**

**26mm Inner Width For CX/Gravel**

**Pillar 1423 Spokes, Aero & Strong**

**Front 24/Rear 24 Spokes**




**ProX 26mm Inner Width Mid-range C52DB Disc Brake 700C Gravel Carbon Wheels**

Model	<b>C52DB-PXG26-40C-1423</b>	<b>C52DB-PXG26-45C-1423</b>	<b>C52DB-PXG26-50C-1423</b>
Rim Drawing			
Rim Depth	40mm	45mm	50mm
Rim Width	32mm Outer (26mm Inner)	32mm Outer (26mm Inner)	32mm Outer (26mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX C52DB	ProX C52DB	ProX C52DB
Front Size	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle
Rear Size	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle
Spoke	Pillar 1423	Pillar 1423	Pillar 1423
Tire Size (Recommended)	700*35C-50C	700*35C-50C	700*35C-50C
Weight (+/-3%)	1500g	1540g	1580g

Bead Hook and Hookless rims optional

Pillar 1423 spokes, Aero&strong

Front 24/Rear 24 Spokes



ProX 98DB Economical Disc Brake Hubs

6-Pawl Freehub System  
Shimano 11/12s or SRAM 12s XDR Optional

Compatible for 700\*30C-50C tire (tubeless ready)

**ProX Affordable 98DB Disc Brake 700C Gravel Carbon Wheels**

Model	98DB-PCX33-1423	98DB-PZX33-1423	98DB-PCX44-1423	98DB-PZX44-1423
Rim Drawing				
Rim Depth	33mm	33mm	44mm	44mm
Rim Width	28mm Outer (21mm Inner)	28mm Outer (23mm Inner)	28mm Outer (21mm Inner)	28mm Outer (23mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX 98DB	ProX 98DB	ProX 98DB	ProX 98DB Disc
Front Size	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle
Rear Size	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle
Spoke	Pillar 1423	Pillar 1423	Pillar 1423	Pillar 1423
Tire Size (Recommended)	700*30C-50C	700*30C-50C	700*30C-50C	700*30C-50C
Weight (+/-3%)	1487g	1487g	1547g	1547g

89MB Light Weight MTB Carbon Wheels

Front 28/Rear 28 Spokes

Tubeless Ready



DT Swiss Hubs Optional

89MB Disc Brake Hubs - Steel Bearings  
Shimano 11s/Microspline/12s SRAM XD

Ratchet 54T Freehub System

Pillar 1423 Spokes, Strong and Stiff

**ProX Light Weight 89MB Wheels Carbon MTB Wheels Ratchet 54T Mountain Bike Wheels**

Model	89MB-PAD930-1423	89MB-PAD930GP-1423	89MB-PAD933-1423	89MB-PAD933GP-1423	89MB-PAD938-AM-1423	89MB-PAD940-1423
Rim Drawing						
Rim Offset	2.6mm	2.6mm	3mm	3mm	3mm	3.5mm
Rim Width	30mm Outer (25mm Inner)	30mm Outer (25mm Inner)	33mm Outer (26mm Inner)	33mm Outer (26mm Inner)	38mm Outer (32mm Inner)	40mm Outer (34mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX 89MB	ProX 89MB	ProX 89MB	ProX 89MB	ProX 89MB	ProX 89MB
Front Size	15*110mm Boost	15*110mm Boost	15*110mm Boost	15*110mm Boost	15*110mm Boost	15*110mm Boost
Rear Size	12*148mm Boost	12*148mm Boost	12*148mm Boost	12*148mm Boost	12*148mm Boost	12*148mm Boost
Spoke	Pillar 1423	Pillar 1423	Pillar 1423	Pillar 1423	Pillar 1423	Pillar 1423
Tire Size (Recommended)	29*2.0"-2.4"	29*2.0"-2.4"	29*2.1"-2.5"	29*2.1"-2.5"	29*2.3"-2.8"	29*2.35"-3.0"
Weight (+/-3%)	1472g	1372g	1512g	1432g	1652g	1732g

ProX 88MB MTB Boost Hub  
6-bolt and Center Lock optional

Ratchet Freehub System  
Shimano 11s, Microspline 12s or SRAM XD optional

Tubeless Ready

DT Swiss Hubs Optional

XC/TR/AM/EN rims optional

Pillar 1423 spokes, strong&stiff

Front 28/Rear 28 Spokes



**ProX 88MB Wheels Carbon MTB Wheels Ratchet 36T Mountain Bike Wheels**

Model	88MB-PAD930-1423	88MB-PAD930GP-1423	88MB-PAD933-1423	88MB-PAD933GP-1423	88MB-PAD938-AM-1423	88MB-PAD940-1423
Rim Drawing						
Rim Offset	2.6mm	2.6mm	3mm	3mm	3mm	3.5mm
Rim Width	30mm Outer (25mm Inner)	30mm Outer (25mm Inner)	33mm Outer (26mm Inner)	33mm Outer (26mm Inner)	38mm Outer (32mm Inner)	40mm Outer (34mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX 88MB	ProX 88MB	ProX 88MB	ProX 88MB	ProX 88MB	ProX 88MB
Front Size	15*110mm Boost	15*110mm Boost	15*110mm Boost	15*110mm Boost	15*110mm Boost	15*110mm Boost
Rear Size	12*148mm Boost	12*148mm Boost	12*148mm Boost	12*148mm Boost	12*148mm Boost	12*148mm Boost
Spoke	Pillar 1423	Pillar 1423	Pillar 1423	Pillar 1423	Pillar 1423	Pillar 1423
Tire Size (Recommended)	29*2.0"-2.4"	29*2.0"-2.4"	29*2.1"-2.5"	29*2.1"-2.5"	29*2.3"-2.8"	29*2.35"-3.0"
Weight (+/-3%)	1515g	1415g	1555g	1475g	1695g	1775g




**ProX New 32 Inch 89MB Wheels Carbon MTB Wheels Ratchet 54T For XC/AM**

Model	89MB-AD32-36-Leader	89MB-AD32-36SL-Leader
Rim Drawing		
Rim Offset	2.8mm	2.8mm
Rim Width	35.8mm Outer (30mm Inner)	35.8mm Outer (30mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX 89MB	ProX 89MB
Front Size	15*110mm Boost	15*110mm Boost
Rear Size	12*148mm Boost	12*148mm Boost
Spoke	Sapim Leader	Sapim Leader
Tire Size (Recommended)	32*2.3"-2.8"	32*2.3"-2.8"
Weight (+/-3%)	1814g	1734g






**ProX 3-Spoke Carbon Wheels For Road/TT/Track Bikes**

Model	<b>P3-705</b>	<b>P3-758</b>	<b>P3-120C</b>
Rim Drawing			
Rim Depth	70-75mm	75-80mm	120mm
Rim Width	28mm Outer (21mm Inner)	28mm Outer (22.5mm Inner)	28mm Outer (22.5mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX 36DB	ProX 36DB	ProX 36DB
Front Size	12*100mm Thru-Axle	12*100mm Thru-Axle	12*100mm Thru-Axle
Rear Size	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle
Spoke	3-Spoke Carbon	3-Spoke Carbon	3-Spoke Carbon
Tire Size (Recommended)	700*28C-45C	700*28C-45C	700*28C-45C
Weight (+/-3%)	F:950g   R:1050g	F:950g   R:1050g	F:950g   R:1050g





**ProX 5-Spoke Carbon Wheels and Full Disk Rear Wheel**

Model	<b>P5-52C DB</b>	<b>P5-38C DB</b>	<b>UFO27-DISC</b>
Rim Drawing			
Rim Depth	52mm	38mm	N/A
Rim Width	25mm Outer (18mm Inner)	28mm Outer (21.6mm Inner)	27mm Outer (21mm Inner)
Tire Type	Tubeless or Clincher	Tubeless or Clincher	Tubeless or Clincher
Hub	ProX 36DB	ProX 36DB	ProX 36DB
Front Size	12*100mm Thru-Axle	12*100mm Thru-Axle	N/A
Rear Size	12*142mm Thru-Axle	12*142mm Thru-Axle	12*142mm Thru-Axle
Spoke	5-Spoke Carbon	5-Spoke Carbon	Full Disk
Tire Size (Recommended)	700*25C-40C	700*28C-50C	700*28C-45C
Weight (+/-3%)	F:850g   R:950g	F:625g   R:725g	970g




**ProX 29mm Wide Disc Brake 700C Carbon Clincher Rims 23mm Inner Width**

Model	PRD923-38C	PRD923-45C	PRD923-50C	PRD923-55C	PRD923-60C
Sectional Drawing					
Rim Depth	38mm	45mm	50mm	55mm	60mm
Rim Width	28.5mm Outer (23mm Inner)	28.5mm Outer (23mm Inner)	28.5mm Outer (23mm Inner)	28.5mm Outer (23mm Inner)	28.5mm Outer (23mm Inner)
Weight(±15g)	390g	400g	430g	460g	480g
Terrain (Recommended)	Road	Road	Road	Road	Road
ERD	564mm	550mm	540mm	530mm	520mm
Material	T700+T800	T700+T800	T700+T800	T700+T800	T700+T800
Max Weight Limit	115kg/253lb	120kg/265lb	120kg/265lb	120kg/265lb	125kg/275lb
Max Spoke Tension	130kgf	130kgf	130kgf	130kgf	130kgf
Max Tire Pressure	125psi/8.6bar	125psi/8.6bar	125psi/8.6bar	125psi/8.6bar	125psi/8.6bar
Tire Size (Recommended)	700*30C-50C	700*30C-50C	700*30C-50C	700*30C-50C	700*30C-50C



**ProX Carbon Gravel Rims Widened 26mm/32mm Inner Width 700C Gravel Bike Rims**

Model	PXG26-40C	PXG26-45C	PXG26-50C	PXG32-40C	PXG32-45C	PXG32-50C
Sectional Drawing						
Rim Depth	40mm	45mm	50mm	40mm	45mm	50mm
Rim Width	31.5mm Outer (26mm Inner)	31.5mm Outer (26mm Inner)	31.5mm Outer (26mm Inner)	37.5mm Outer (32mm Inner)	37.5mm Outer (32mm Inner)	37.5mm Outer (32mm Inner)
Weight(±15g)	410g	430g	450g	430g	440g	460g
Terrain (Recommended)	CX/Gravel	CX/Gravel	CX/Gravel	CX/Gravel	CX/Gravel	CX/Gravel
ERD	560mm	550mm	540mm	560mm	550mm	540mm
Material	T700	T700	T700	T700	T700	T700
Max Weight Limit	120kg/265lb	120kg/265lb	120kg/265lb	120kg/265lb	120kg/265lb	120kg/265lb
Max Spoke Tension	130kgf	130kgf	130kgf	130kgf	130kgf	130kgf
Max Tire Pressure	90psi/6.2bar	90psi/6.2bar	90psi/6.2bar	90psi/6.2bar	90psi/6.2bar	90psi/6.2bar
Tire Size (Recommended)	700*35C-50C	700*35C-50C	700*35C-50C	700*44C-70C	700*44C-70C	700*44C-70C



**ProX 32er MTB Carbon Rims 32inch Mountain Bike Carbon Rims For XC/AM**

Model	<b>AD32-36SL</b>	<b>AD32-36</b>
Sectional Drawing		
Rim Depth	2.8mm	2.8mm
Rim Width	35.8mm Outer (30mm Inner)	35.8mm Outer (30mm Inner)
Weight(±15g)	460g	500g
Terrain (Recommended)	Cross Country and All Mountain	Cross Country and All Mountain
ERD	646mm	646mm
Material	T700+T800	T700
Max Weight Limit	100kg/220lb	120kg/265lb
Max Spoke Tension	145kgf	145kgf
Max Tire Pressure	40psi/2.7bar	40psi/2.7bar
Tire Size (Recommended)	32*2.3"-2.8"	32*2.3"-2.8"